

WristOx₂[®] Model 3150 USB

Wrist-Worn Pulse Oximeter



Product Highlights

- Available in two configurations:
 - WristOx₂ Model 3150 USB device with sensor of choice and carrying case
 - Starter Kit (3150SK USB) with WristOx₂ Model 3150 USB device, sensor of choice, nVISION software, PC USB interface cable, extra wrist straps and carrying case
- WristOx₂ line of sensors is designed exclusively for use with the WristOx₂ Model 3150 USB
- Easy-to-use: simply put your finger in the sensor to begin monitoring and recording data
- Small size wears like a watch with large display screen and enhanced sensor connector design
- Overnight oximetry reporting available when used with Nonin nVISION[®] data management software
- Data can be transferred securely to nVISION via USB connection

The WristOx₂ Model 3150 USB Pulse Oximeter Delivers More Value as a Lower-Cost Solution

Designed using Nonin Medical's proven PureSAT[®] SpO₂ technology, the WristOx₂ Model 3150 USB delivers fast, highly accurate oxygen saturation and pulse rate readings in challenging conditions including low perfusion and motion.

Because of its USB data connection and lower price, the WristOx₂ Model 3150 USB provides added value over the WristOx₂ Model 3150 to customers who do not require the use of Bluetooth[®].

The WristOx₂ Model 3150 USB comes with a wide range of Nonin PureLight[®] sensors and provides continuous and reliable SpO₂ monitoring and data recording, making it ideal for overnight oximetry studies at home, in the hospital and in sleep labs.



Added Benefits

Versatility – The WristOx₂ Model 3150 USB is an ideal choice for multiple applications where small, portable oximetry is needed and Bluetooth® connectivity is not essential.

Simple Data Verification – The Memory Volume Indicator (MVI) Mode provides a graphic display in hours and minutes, verifying that a sufficient amount of data has been recorded during oxygen qualification testing.

Comparison of Full and MVI Display



Full Display Showing SpO₂ and Heart Rate



MVI Display Showing Monitoring Time in Hours and Minutes

Powerful Battery – 48 hours of battery life using two AAA alkaline batteries

Enhanced Memory – 1,080 hours of non-volatile memory at a four-second sampling rate with additional high resolution variable sampling options of one or two seconds

Nonin Quality and Support – Rugged durability and industry-leading 3-year warranty

Select Your Options

Starter Kit 3150SK USB

- WristOx₂ Model 3150 USB device
- Sensor of choice (see right)
- Carrying case
- 3 extra wristbands
- nVISION Software
- PC USB interface cable




WristOx₂ Model 3150 USB

- WristOx₂ Model 3150 USB device
- Sensor of choice (see right)
- Carrying case
- 1 wristband



Adult Flex System

8000J-WO₂



Soft Sensor

8000SL-WO₂, 8000SM-WO₂, 8000SS-WO₂



Adult Clip Sensor

8000AA-WO₂ Adult

Specifications

Dimensions (without sensor or strap)56 mm (2.2") wide x 74 mm (2.91") high x 20 mm (.79") thick
Weight (with batteries and wrist strap)71 grams (2.5 oz)
Warranty3 years
Oxygen Saturation Range (%SpO ₂)0% to 100%
Pulse Rate Range18 to 321 pulses per minute
Displays	
Numeric Displays3-digit Indicators
Pulse IndicatorPulse Strength Bar graph
Accuracy	
Blood Oxygen Saturation (%SpO ₂ ±1 A _{rms})*	.70% to 100%
Non-motion± 2 digits**
Low perfusion± 2 digits**
Motion± 3 digits***
Pulse Rate (in all 3 listed above)± 3 digits**
Temperature	
Operating+23° to +104°F (-5° to +40°C)
Storage/Transportation-40° to +158°F (-40° to +70°C)
Humidity	
Operating10% to 95% noncondensing
Storage/Transportation10% to 95% noncondensing
Altitude	
Operating AltitudeUp to 13,123 feet (4,000 meters)
Hyperbaric PressureUp to 4 atmospheres
Power RequirementsTwo 1.5V alkaline AAA batteries
Battery Life	
Operating53 hours minimum
Storage9 months
Memory	
TypeNonvolatile
CapacityUp to 1,080 hours @ 4 sec. data storage rate Up to 540 hours @ 2 sec. data storage rate Up to 270 hours @ 1 sec. data storage rate

Classifications per IEC 60601-1/UL60601-1

Type of ProtectionInternally powered (on battery power)
Degree of ProtectionType BF-Applied Part
Mode of OperationContinuous

* ± A_{rms} encompasses approximately 68% of the population.

** Refer to the operator's manual for additional accuracy specifications.

*** As tested with Soft Sensor Series.

Quality systems registered to ISO 13485

Refer to the Instructions for Use for complete information, warnings, cautions and specifications for the product you are using.

Specifications are subject to change without notice.

Authorized Distributor:

For more information please contact us at:

Air Liquide Healthcare, Stratus House, Unit 1 IDA College Park, Blanchardstown Road North, Blanchardstown, Dublin 15, D15 PEC4.
Tel: +353 (0)1 809 1800 Freephone: 1800 24 02 02 (ROI only)
0800 328 5875 (NI only). Fax: +353 (0)1 829 3966
Email: healthie@airliquide.ie Website: www.airliquidehealthcare.ie



Nonin Medical, Inc.
13700 1st Avenue North
Plymouth, MN • 55441 • U.S.A.
Tel: +1.763.553.9968 1.800.356.8874
Fax: +1.763.577.5521
E-mail: info@nonin.com

nonin.com



Nonin Medical B.V.
Prins Hendriklaan 26
1075 BD Amsterdam • Netherlands
Tel: +31 (0)13 - 79 99 040
Fax: +31 (0)13 - 79 99 042
E-mail: infointl@nonin.com

